

INFORMATION REPORT INFORMATION REPORT

CENTRAL INTELLIGENCE AGENCY

This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C. Secs. 793 and 794, the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

C-O-N-F-I-D-E-N-T-I-A-L
NOFORN

25X1

COUNTRY	USSR (Leningrad Oblast)	REPORT	
SUBJECT	Testing Equipment at the Leningrad Construction Engineering Institute	DATE DISTR.	15 October 1958
	<i>ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED PLEASE ROUTE</i>	NO. PAGES	1
		REFERENCES	RD
DATE OF INFO.			25X1
PLACE & DATE ACQ.			25X1

SOURCE EVALUATIONS ARE DEFINITIVE. APPRAISAL OF CONTENT IS TENTATIVE.

A listing of equipment used for structural tests at the Leningrad Order of Labor Red Banner Construction Engineering Institute

25X1

The listing includes the Soviet designations for equipment and instruments, a brief note on the characteristics and purpose of the equipment, and a reference to the plant or institution responsible for its production.



(I)

PE

25X1

PROCESSED COPY

ACM

Please evaluate

S

TCS

LY/so

C-O-N-F-I-D-E-N-T-I-A-L
NOFORN

STATE	X	ARMY	X	NAVY	X	AIR	X	FBI		AEC		ORR/EV	X	
(Note: Washington distribution indicated by "X"; Field distribution by "#".)														

INFORMATION REPORT INFORMATION REPORT

25X1

Page Denied

Next 1 Page(s) In Document Denied

Following is a list of the basic equipment and instruments used for structural tests in the Mechanical Laboratory of the Leningrad Institute of Civil Engineering. 3

CONFIDENTIAL -
NOFORN

Construction
Engineering
Institute

Make

per
OCIE/FR.

No.	Name	Technical characteristics and purpose	
MACHINES			
1.	Universal testing machine for 50 ton with the pulsator for 25 ton. Type / RM-1	Tensile, compression and bent tests under the static load up to 50 ton and the pulsating load up to 25 ton with the frequency up to 600 c.p.m. Error in the readings of dynamometer $\pm 1\%$	The plant "3 M" Annavir
2.	Universal testing machine for 50 ton. Type /4 M-50	Tensile, compression and bent tests under the static load up to 50 ton	The Kharkov Poly-technical Institute
3.	Machine for fatigue testing of metals by bending. Type "H4"	Fatigue testing of round sample by bending combined with shear	The Ministry of Machines and Instrument Industry
4.	Gagarin's press for the leading up to 5 ton	Compression - Tension tests (with reverser) of small samples (3 - 6 mm) with diagram plotting	
5.	X-ray unit of УМРЛ -10 type	X-ray examination of materials to find defects	Ministry of Electrical Industry, USSR

C O N F I D E N T I A L

N O F O R M

6. Machine for tensile strength tests for 250 kg load. Type PMM 250 Tensile strength tests of various materials with the high deformation ability The Ministry of Chemical Industry, USSR, the plant "Metallist," Leningrad

7. Machine for tensile strengths for 5 ton. Type P-5 Tensile strength tests of materials The plant "3 M" Armavir

INSTRUMENTS

1. Oscillograph M 10-2 with eight loops Recording of dynamic processes of the frequency up to 5000 c.p.s. with simultaneous recording of 8 processes "Vibrator"

2. Enlarger M-10 for the oscillograph M 0-2 Five times enlargement of the oscillograms of the oscillograph M 0-2 "Vibrator"

3. Device for measuring plasticity. Type UD-2 Measurements of static elasticity with resistance pick-ups, sensitivity 10-5 The plant: "Krasny Isobretatal."

4. Three channel tensometric unit Investigation of dynamic processes with the help of resistance pick-ups. Frequency of the oscillations recorded up to 1000 c.p.s. Electrotechnical Institute, Leningrad

5. Eight channel tensometric unit 8 AH4-7/1 The same with the frequency recorded up to 1000 c.p.s. Same as above

6. Ball hardness gauge Brinell hardness test. Tolerable error $\pm 1\%$ The plant "Krasnolit" Krasnodar

7. Aistov's calibrating machine. Type 4K 1 A-5 Calibration of tensometers. Precision $\pm 0.1\%$ The Leningrad Institute of Civil Engineering

8. Dushenkov's comparator. Type KD-2 Field deformation tests. Precision $\pm 10\%$ Same as above

9. Aistov's tensometer. Type T-A-2 Deformation measurements under laboratory and field conditions. Precision $\pm 1\%$ Same as above

10. Aistov's tensoshearometer. Type TCA Measurements of longitudinal and shear deformation. Precision $\pm 1\%$ Same as above

11. Aistov's device for measurement of linear deformation of the samples made of raw concrete during their solidification. Precision 1 μ Same as above

12. Aisov's clinometer. Type KA-4 Measurement of incline level of structures. Precision $\pm 0.02 - 0.04$ mm Same as above

13. Aistov's deflectometer. Type 11-A-3 Measurement of displacement of separate points of structures. Precision $\pm 0.02 - 0.04$ mm Same as above

-3-

C O N F I D E N T I A L
N O F O R M

14. Polarization projector. Type ПП 0-4	Optical investigation of stress	Leningrad State University
15. Vibroscope "BK"	Investigation and elimination of vibration	Leningrad Tool Plant
16. Ultrasonic defect detector. Type Р4-8Р	Investigation of defects in sheet material	
17. Horizontal optical indicator КГ	Measurement of linear strength. Precision ± 0.0002 mm	OM3
18. Vertical optical indicator HB Г with the head KHK	Measurement of linear strength. Precision ± 0.0002 mm	OM3
19. High precision level HA-1	High precision levelling	OM3

C O N F I D E N T I A L
N O F O R M

-4-

Following is a list of equipment of the Laboratory of Continuous Tests of the Leningrad Institute of Civil Engineering.

1. Machine for tensile strength tests with the capacity five tons of "P-5" type of screw action with hand and electric drive, for standard testing of wooden samples. Range of measurement 200-5000 kg. The machine has four side scales with the ranges: from 200 to 500 kg.
from 200 to 1000 kg.
from 250 to 2500 kg.
from 500 to 5000 kg.
The maximum distance between the clamps is 750 mm. The machine is made by the Armavir testing equipment plant.
2. Installation for bent testing with long time leading of 10 standard wooden samples. The leading is applied to the sample at the two points through the levers with the ratio 1 : 7. The installation is made according to the drawings by the Central Research Institute of Structures, Moscow.
3. Universal installation for continuous tensile, compression and bent testing of eight standard wooden samples. The load is applied to the samples through the levers with 20 - fold ratio (1:20). The installation is made by the Institute of Construction Mechanisms, Kiev.
4. Installations for continuous tensile and compression testing of one standard sample. Leading is applied to the sample through the levers with 20-fold ratio (1:20). The installation is made by the Experimental Plant of the Central Research Institute of Mechanical Treatment of Timber, Moscow.

CONFIDENTIAL

N O F O R N